

These hydraulic cutters are equipped with blades designed for wire rigging up to 16 mm. They are lightweight but powerful, and extremely easy to operate. The integrated hand pump ensures a very compact design.

The cutters are supplied in a waterproof dry-bag, protected and ready for action.





These models share the same compact design as our wire cutters, but are fitted with blades and a cutting head specially developed for Rod up to -30 (11.1 mm). These hydraulic cutters are lightweight but powerful, and extremely easy to operate.

The cutters are supplied in a waterproof dry-bag, protected and ready for action



Cutting a rig can be hazardous, but is sometimes essential to prevent further damage or loss of life. For emergency situations like this, Holmatro has developed a special range of remote-operated cutters.

Equipped with blades designed for Rod rigging up to -115 (22.2 mm), the cutters lock onto the rig and remain in place unattended. A hydraulic hand pump connected by a three metre hose allows the operator to stand back from any flying ends if the rig is cut under tension.

Supplied in a waterproof protective case with wheels and retractable handle for easy transportation.



Manual wire cutters

model	capacity	max. cutting size: wire		max. cutting size dyform		pump	storage	weight	
		mm	inch	mm	inch			kg	lb
EWC14H	14 - 16	16	0,56	14	0,55	integrated	dry-bag	2,8	6,2
EWC16H	16 - 20	20	0,63	16	0,63	integrated	dry-bag	4,9	10,8

Manual Rod cutters

model	capacity	max. cutting size: Rod		pump	storage	weight	
		mm	inch			kg	lb
ERC-12H	-12	7,1	0,281	integrated	dry-bag	2,8	6,4
ERC-30H	-30	11,1	0,437	integrated	dry-bag	4,9	12,4

Remote manual Rod cutters

model	capacity	max. cutting size: Rod		hose length	pump	storage	weight	
		mm	inch	m			kg	lb
ERC-30R	-30	11,1	0,437	3,0	remote	case	3,1	6,8
ERC-60R	-60	16,8	0,660	3,0	remote	case	6,6	14,6
ERC-115R	-115	22,2	0,875	3,0	remote	case	15,8	34,8